



# 2030ES Electric Scissor Lift



## QUESTIONS TO ASK

- What is the floor loading in the work area?
- Do you want to work multiple shifts?
- Do you need to move up and down ramps?
- Do you need to enter narrow doors?
- Do you need an extension lead outlet in the platform?
- Are you working in a food or clean environment and can't have oil fumes?

## KEY SELLING POINTS

- Smooth control, proportional drive, lift and lower
- Long battery duty cycles, drive at full elevation for 18 hours
- 76cm wide chassis allows drive through a standard 81cm door
- Fold down rails allows drive through standard 203cm door
- Extension platform has fold down rails
- Non marking solid tyres with tight turning circle, zero inside turning radius
- Constant traction control with quiet electric front wheel drive for 25 per cent gradeability
- Removable/Interchangeable control box with all other ES scissors
- Weatherproof Inverter style battery charger, can use long extension lead. Ideal for multi shift applications
- Wide scissor stack provides rigidity and stability
- Pothole protection prevents elevated drive
- Multi axis 3 degree level sensor with a lateral slope range of 3 degree at base to 2 degree fully elevated
- Diagnostic Battery Meter at base or JLG analyser indicates system functions for servicing and adjustment

## APPLICATIONS

- Facilities maintenance
- Shopping centres and other indoor/outdoor areas.
- Manufacturing and warehouse applications and stock-takes
- Telecommunications facilities
- Entertainment facilities
- Electricians
- Plumbers
- All maintenance and construction work
- Outdoors rated 1 person

## SPECIFICATIONS

### Performance:

Platform Height (max.)	6.10m
Working Height	8.10m
Lift Time	30 sec
Lower Time	30 sec
Platform Capacity Standard	360kg

### Dimensions:

Stowed Height - Rails Up	2.20m
Stowed Height - Rails Lowered	1.82m
Minimum Transport Length	2.30m
Minimum Transport Height	1.82m
Overall Width	0.76m
Wheelbase	1.88m
Ground Clearance	0.09m
Platform Width	0.76m
Platform Length	2.30m
Standard Platform Extension	0.9m
Platform Height Lowered	1.10m
Maximum Drive Height	6.10m

### Power:

Power Source	Battery
DC Voltage	24V
DC Power	225 Amp h
Hydraulic Pump - Type	Gear
Batteries	4 x 6V
Charger Electronic IP46 Input Voltage	190-250 VAC

### Travel:

Tyre Size	406 x 125
Tyre Type (Non-Marking)	Solid
Inside Turn Radius	0m
Outside Turn Radius	2.06m
Drive Speed Elevated	0.8km/h
Gradeability	25%
Indoor Rating Person on Platform	2
Outdoor Rating 12.5m/sec Persons on Platform	1
Elevated Drive Time	18 hr

### Weights and Capabilities:

Hydraulic Tank Capacity	4.73 Ltr
Operating Weight	2,065kg



**Ph: 1300 87 44 73**

**UNIT 13 & 14, 61-63 Regentville Road,  
Jamisontown, NSW 2750**