

# THE SULLAIR 425

All the benefits of the Sullair Rotary Screw range combined with maximum portability

The Sullair 425 compressor is the convenient choice for work on the go.

The removable modular canopy and adjustable height hitch give you the flexibility to customise on-site. And with the choice of DPQ road registration capability or a DLQ skid base for flat-bed transportation, you're in charge of where you take it and how you get it there.



Guaranteed Air End longevity and quiet performance from below-freezing to 50°C



Fully customisable, switch from low to high pressure with no need for a toolkit

## TECHNICAL SPECIFICATIONS

| MODEL    | MAX PRESSURE |     | CAPACITY - FREE AIR DELIVERY |                     |     | MOTOR RATING |     | NOISE LEVEL DB(A) | DIMENSION          | APPROX WEIGHT | AIR OUTLET DISCHARGE SIZE | Tyre SIZE (LOAD RANGE) |
|----------|--------------|-----|------------------------------|---------------------|-----|--------------|-----|-------------------|--------------------|---------------|---------------------------|------------------------|
|          | PSI          | BAR | L/s                          | M <sup>3</sup> /Min | CFM | kW           | HP  |                   | L x W x H (mm)     | kg            |                           |                        |
| 425A DPQ | 125          | 8.6 | 200                          | 12                  | 425 | 97           | 130 | 76                | 3966 x 1960 x 1980 | 2005          | 1 x 2"; 3 x ¾"            | 225/75D15              |
| 425A DLQ |              |     |                              |                     |     |              |     |                   | 2710 x 1506 x 1660 | 1894          |                           |                        |
| 425H DPQ | 150          | 10  |                              |                     |     | 104          | 140 |                   | 3966 x 1960 x 1980 | 2014          |                           |                        |
| 425H DLQ |              |     |                              |                     |     |              |     |                   | 2710 x 1506 x 1660 | 1903          |                           |                        |

DLQ - No running gear. Provided with forklift slots  
 DPQ - Highway towable running gear, 2 wheels and enclosure